

Princeton University
COS 217: Introduction to Programming Systems
DT Algorithms

1. int DT_insert(const char* pcPath);

Step 1) If the DT is not initialized, return `INITIALIZATION_ERROR`.

Step 2) Build a Path object for the path that we want to insert. Find farthest Node reachable from the root following the given path (static function `DT_traversePath`).

If traversal fails, free the path and return the failure status back up to the caller.

If traversal result (`oNCurr`) is `NULL`, but the root is not `NULL`, then return `CONFLICTING_PATH`.

Calculate the “depth” of `oNCurr`. (Implicitly 0 if `oNCurr` is `NULL`: new root)

If `oNCurr` is the node with the path we want, return `ALREADY_IN_TREE`.

Otherwise, `oNCurr` is going to be Parent of the next node to be added

Step 3) Starting at Node’s depth + 1 (or at 1 if Node is `NULL`), for each depth until we reach the depth of the final path that we want to insert:

Create a new Path object that is a prefix at that depth of the final path

Create a new node at that depth (`oNNewNode`) with the new prefix Path as its path and `oNCurr` as its parent. If `oNNewNode` fails, free the paths, free any nodes already made here in step 3, and return the failure status back up to the caller.

Otherwise, the newest node is now `oNCurr`. Keep track of the new nodes we’ve added here in step 3 (in case one eventually fails and we have to delete them all)

Continue with the next iteration of Step 3 at the next depth.

Step 4) Once we have added all the new nodes to reach our final path that we wanted:

If the `oNRoot` state variable is `NULL`, set the first new node we made as root

Add the number of new nodes to the data structure’s `ulCount` state variable

Return `SUCCESS`.

2. `int DT_rm(const char *pcPath);`

Step 1) Get a pointer to the Node with the path we want to remove. (Use helper function `DT_findNode`, which traverses path as far as it can. If `DT_findNode` gets all the way to the Node we want to remove, it returns `SUCCESS` and sets a pointer to that Node. Otherwise, it returns an error status that is further returned by `DT_rm`:

If the DT is not initialized: `INITIALIZATION_ERROR`

If it cannot create the Path object, the error status from the Path module

If it cannot traverse all the way to path we want: `NO_SUCH_PATH`

Step 2) Call `Node_free` on the Node found by `findNode` to delete the entire hierarchy rooted at that node. `Node_free` will return the number of nodes removed.

Step 3) `Node_free` removes its parameter Node from that Node's parent's list of children. This will disconnect the Node from the DT.

If the parameter Node has no parent (i.e., it's the root), this step is not done.

Step 4) For every element in the Node's list of children, call `Node_free` recursively on that Child (i.e., goto step 2, but on a child instead of the Node returned by `findNode`) to remove that sub-hierarchy.

Accumulate the return values from all recursive calls to count total number of nodes removed.

Step 5) Once all of this Node's children have been recursively destroyed:

free the now-empty DynArray

free Node's path object

free the Node itself

Return the total count of nodes removed (including this Node itself).

Step 6) Once all the recursion finishes and the `Node_free` call on the original pointer found by `findNode` returns (finally!) back to `DT_rm`:

Decrement the DT's `ulCount` by the number of nodes removed

If the count is now 0 (i.e., we removed the root), set the DT's root to `NULL`

Return `SUCCESS`